AiA223 & AiA233

Filter Housing with DPI

Materials Aluminium
Pressure 17 Bar
Ports 1/4" or 1/2"

Element 25.127. □ & 25.178. □

AiA223 & AiA233 series filter housings with differential pressure indicators have an anodised aluminium head and bowl with polyamide internals.

They are supplied with 1/4" or 1/2" ports and have a range of drain options. These housings are suitable for compressed air systems and general filtration applications.

Standard housings have NPT ports and Viton seals. Other seal types are available as an option. BSPT and BSPP port types are also available.





Technical Specifications

Housing Model	AiA233.201	AiA233.211	AiA233.261	AiA223.271	AiA233.401	AiA233.411	AiA233.461	AiA223.471
Port Size	1/4" NPT	1/4" NPT	1/4" NPT	1/4" NPT	1/2" NPT	1/2" NPT	1/2" NPT	1/2" NPT
Drain	None	1/8" NPT	Manual	Automatic	None	1/8" NPT	Manual	Automatic
Maximum Pressure, Bar	17	17	17	17	17	17	17	17
Maximum Temperature, °C	120	120	120	120	120	120	120	120
Materials of Construction (1)								
Head & Bowl	AL							
Internals	PA							
Seals (2)	Viton							
Filter Element Code (3)	25.178.□	25.178.□	25.178.□	25.127□	25.178.□	25.178.□	25.178.□	25.127□
Adsorber Cartridge Code (4)	25.178.AT□	25.178.AT□	25.178.AT□	-	25.178.AT□	25.178.AT□	25.178.AT□	-
Principal Dimensions in mm								
Diameter	62	62	62	62	62	62	62	62
Height	297	297	309	309	297	297	309	309
Volume, cc	240	240	240	240	240	240	240	240
Weight, kg	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35
Accessories								
Mounting Bracket	MBAiN21							

Notes

(1) Material abbreviations, AL = Aluminium, PA = Polyamide

 $(2) Add \ suffix for \ other \ seal \ types, Chemraz = .C, \ Nitrile = N, \ Kalrez = .K, \ EPDM = .E, \ Silicone = .S, \ (e.g. \ AiA233.201.E)$

(3) Replace the \square with the grade required, e.g. 25.178.5CK, 25.178.520V, 25.178.T20

(4) Replace the \Box with the type required, e.g. 25.178.AT01