


Male Connector (NPT Tapered)
DMC-N



Form C stud end

Series	Part No.	Tube O.D.	H	h	L	l	l ₁	T R(PT), G(PF)	PN(bar)		
									C.Steel	SS316	BRASS
LL	DMC 04LL - 01N	4	10	11	28	18.5	9.9	1/8 - 27.0	100	100	
	DMC 06LL - 01N	6	12	11	28	16.5	9.9	1/8 - 27.0	100	100	63
	DMC 08LL - 01N	8	14	12	30	18.5	9.9	1/8 - 27.0	100	100	63
L	DMC 06L - 01N	6	14	12	32	17.0	9.9	1/8 - 27.0	315	315	200
	DMC 06L - 02N	6	14	17	38	23.0	14.2	1/4 - 18.0	315	315	200
	DMC 08L - 02N	8	17	17	38	23.0	14.2	1/4 - 18.0	315	315	200
	DMC 10L - 02N	10	19	17	39	24.0	14.2	1/4 - 18.0	315	315	200
	DMC 10L - 03N	10	19	19	40	25.0	14.2	3/8 - 18.0	315	315	
	DMC 12L - 02N	12	22	19	40	25.0	14.2	1/4 - 18.0	315	315	200
	DMC 12L - 03N	12	22	19	40	25.0	14.2	3/8 - 18.0	315	315	200
	DMC 12L - 04N	12	22	22	45	30.0	19.1	1/2 - 14.0	315	315	200
	DMC 15L - 04N	15	27	24	46	31.0	19.1	1/2 - 14.0	315	315	200
	DMC 18L - 04N	18	32	27	48	31.5	19.1	1/2 - 14.0	315	315	200
	DMC 22L - 06N	22	36	32	50	33.5	19.1	3/4 - 14.0	160	160	100
	DMC 28L - 08N	28	41	41	56	39.5	23.9	1 - 11.5	160	160	100
	DMC 35L - 10N	35	50	46	62	40.5	23.9	1 1/4 - 11.5	160	160	
DMC 42L - 12N	42	60	55	65	42.0	25.4	1 1/2 - 11.5	160	160		
S	DMC 06S - 02N	6	17	17	43	28.0	14.2	1/4 - 18.0	630	630	400
	DMC 08S - 02N	8	19	17	43	28.0	14.2	1/4 - 18.0	630	630	400
	DMC 10S - 02N	10	22	19	44	27.5	14.2	1/4 - 18.0	630	630	
	DMC 10S - 03N	10	22	19	44	27.5	14.2	3/8 - 18.0	630	630	400
	DMC 12S - 02N	12	24	22	46	29.5	14.2	1/4 - 18.0	630	630	
	DMC 12S - 03N	12	24	22	46	29.5	14.2	3/8 - 18.0	630	630	400
	DMC 12S - 04N	12	24	22	51	34.5	19.1	1/2 - 14.0	630	630	400
	DMC 14S - 04N	14	27	24	54	36.0	19.1	1/2 - 14.0	630	630	400
	DMC 16S - 04N	16	30	27	54	35.5	19.1	1/2 - 14.0	400	400	250
	DMC 20S - 06N	20	36	32	59	37.5	19.1	3/4 - 14.0	400	400	250
	DMC 25S - 08N	25	46	41	69	45.0	23.9	1 - 11.5	400	400	
	DMC 30S - 10N	30	50	46	73	46.5	23.9	1 1/4 - 11.5	400	400	
DMC 38S - 12N	38	60	55	80	49.0	25.4	1 1/2 - 11.5	315	315		

Dimensions are given for approximate length with tightened nut. All dimensions are in millimeters for reference only, subject to change.