


Male Connector (BSP Tapered)
DMC-R



Form C stud end

Series	Part No.	Tube O.D.	H	h	K	L	l	l ₁	T R(PT), G(PF)	PN(bar)		
										C.Steel	SS316	BRASS
LL	DMC 04LL - 01R	4	10	11	-	26	16.0	8	PT 1/8	100	100	63
	DMC 06LL - 01R	6	12	11	-	26	14.5	8	PT 1/8	100	100	63
	DMC 08LL - 01R	8	14	12	-	28	16.5	8	PT 1/8	100	100	63
	DMC 08LL - 02R	8	14	14	-	32	20.5	12	PT 1/4	100	100	63
	DMC 10LL - 02R	10	17	14	-	32	20.5	12	PT 1/4	100		63
	DMC 12LL - 02R	12	19	17	-	32	20.0	12	PT 1/4	100		63
	DMC 12LL - 03R	12	19	17	-	32	20.0	12	PT 3/8	100		63
L	DMC 06L - 01R	6	14	12	-	30	15.0	8	PT 1/8	315	315	
	DMC 08L - 02R	8	17	17	-	35	20.0	12	PT 1/4	315	315	
	DMC 10L - 02R	10	19	17	-	36	21.0	12	PT 1/4	315	315	
	DMC 12L - 02R	12	22	19	-	37	22.0	12	PT 1/4	315		200
	DMC 12L - 03R	12	22	19	-	37	22.0	12	PT 3/8	315	315	
	DMC 12L - 04R	12	22	24	-	39	24.0	14	PT 1/2	315	315	200
	DMC 15L - 03R	15	27	24	-	38	23.0	12	PT 3/8	315	250	200
	DMC 15L - 04R	15	27	24	-	40	25.0	14	PT 1/2	315	315	
	DMC 18L - 04R	18	32	27	-	41	25.5	14	PT 1/2	315	250	100
DMC 22L - 06R	22	36	32	-	46	29.5	16	PF 3/4	160	160	100	

Dimensions are given for approximate length with tightened nut. All dimensions are in millimeters for reference only, subject to change.