

## HOSES & PIGTAILS

### FLEXIBLE HOSES WITH CYLINDER CONNECTION ACCORDING BS-341 230 BAR



#### BASIC DESIGN:

- with hex nut, inlet see below, outlet NPT 1/4" male AND ANTI WHIP RESTRAINTS

Art.-Nr.	Type	Material	Specification
H27415201	BS3	SS/ PCTFE	1m length; with safety hose
H27343201	BS4	SS/ PCTFE	1m length; with safety hose
H27508764	BS8	SS/ PCTFE	1m length; with safety hose
H27515064	BS14	SS/ PCTFE	1m length; with safety hose
H27515164	BS15	SS/ PCTFE	1m length; with safety hose

### PIGTAILS WITH CYLINDER CONNECTION ACCORDING. BS-341 -230 BAR



#### BASIC DESIGN:

- with hex nut, spiral tube, inlet see below, outlet NPT 1/4" male

Art.-Nr.	Type	Material	Specification
H27428964	BS3	SS/ PCTFE	Spiral tube, tube Ø 6 mm
H27450064	BS4	SS/ PCTFE	Spiral tube, tube Ø 6 mm

### FLASH BACK ARRESTORS



Art.-Nr.	Type	Inlet x Outlet	Material	Gas / max. pressure (bar)				
				A*	H	M	O	P
L000337	FS400	G1/4"m x G 1/4"f	Brass	-	10	12	-	8
L000454	FS400	G1/4"m x G 1/4"f	Brass-Cr	1.5	3.5	-	15	-
L000110	FS500	NPT 1/4"f x NPT 1/4"m	SS	1.5	3.5	5	15	5
B000096	FS500	NPT 1/4"m x NPT 1/4"f	Brass-Cr	1.5	3.5	-	15	-
B000492	FS500	NPT 1/4"f x NPT 1/4"f	SS	1.5	3.5	5	15	5
B000614	FS500	NPT 1/4"m x NPT 1/4"f	Brass	-	9	12	-	-
B000643	FS500	NPT 1/4"f x NPT 1/4"f	SS	1.5	4	5	-	-
B000892	FS500	NPT 1/4"f x NPT 1/4"f	Brass	1.5	10	12	-	12

\*) Acetylene C<sub>2</sub>H<sub>2</sub> (A), Hydrogen H<sub>2</sub> (H), Methane CH<sub>4</sub> (M), Oxygen O<sub>2</sub> (O), Propane C<sub>3</sub>H<sub>8</sub> (P)