



## Elbow H-SLA



### Female NPT Both Ends.

| Part No.      | Pipe Size | L    | d    | H Width Across Flat | Pressure Rating    |     |       |     |
|---------------|-----------|------|------|---------------------|--------------------|-----|-------|-----|
|               |           |      |      |                     | SS316 Carbon Steel |     | Brass |     |
|               |           |      |      |                     | psig               | bar | psig  | bar |
| H - SLA - 2N  | 1/8       | 24.0 | 8.9  | 12.7                | 6,500              | 447 | 3,200 | 220 |
| H - SLA - 4N  | 1/4       | 29.0 | 11.7 | 17.5                | 6,600              | 454 | 3,300 | 227 |
| H - SLA - 6N  | 3/8       | 34.5 | 15.0 | 20.6                | 5,300              | 365 | 2,600 | 179 |
| H - SLA - 8N  | 1/2       | 37.0 | 18.7 | 25.4                | 4,900              | 337 | 2,400 | 165 |
| H - SLA - 12N | 3/4       | 46.5 | 23.5 | 31.8                | 4,600              | 316 | 2,300 | 158 |
| H - SLA - 16N | 1         | 48.8 | 29.7 | 42.9                | 4,400              | 303 | 2,200 | 151 |


## Street Elbow H-SLC



### Female to Male NPT.

| Part No.      | Pipe Size | L    | L <sub>1</sub> | d    | H Width Across Flat | Pressure Rating    |     |       |     |
|---------------|-----------|------|----------------|------|---------------------|--------------------|-----|-------|-----|
|               |           |      |                |      |                     | SS316 Carbon Steel |     | Brass |     |
|               |           |      |                |      |                     | psig               | bar | psig  | bar |
| H - SLC - 2N  | 1/8       | 24.1 | 19.6           | 4.8  | 12.7                | 6,500              | 447 | 3,200 | 220 |
| H - SLC - 4N  | 1/4       | 29.0 | 26.5           | 7.1  | 17.5                | 6,600              | 454 | 3,300 | 227 |
| H - SLC - 6N  | 3/8       | 34.5 | 28.2           | 9.6  | 20.6                | 5,300              | 365 | 2,600 | 179 |
| H - SLC - 8N  | 1/2       | 37.0 | 35.3           | 11.9 | 25.4                | 4,900              | 337 | 2,400 | 165 |
| H - SLC - 12N | 3/4       | 46.5 | 39.6           | 15.7 | 31.8                | 4,600              | 316 | 2,300 | 158 |
| H - SLC - 16N | 1         | 48.8 | 49.2           | 22.3 | 42.9                | 4,400              | 303 | 2,200 | 151 |


## Reducing Street Elbow H-SLCR



### Female to Male NPT.

| Part No.        | Pipe Size | Male Pipe Size | L    | L <sub>1</sub> | d    | H Width Across Flat | Pressure Rating    |     |       |     |
|-----------------|-----------|----------------|------|----------------|------|---------------------|--------------------|-----|-------|-----|
|                 |           |                |      |                |      |                     | SS316 Carbon Steel |     | Brass |     |
|                 |           |                |      |                |      |                     | psig               | bar | psig  | bar |
| H - SLCR 4 - 2N | 1/4       | 1/8            | 29.0 | 22.4           | 4.8  | 17.5                | 6,500              | 447 | 3,200 | 220 |
| H - SLCR 6 - 4N | 3/8       | 1/4            | 34.5 | 28.2           | 7.1  | 20.6                | 5,300              | 365 | 2,600 | 179 |
| H - SLCR 8 - 4N | 1/2       | 1/4            | 37.0 | 30.5           | 7.1  | 25.4                | 4,900              | 337 | 2,400 | 165 |
| H - SLCR 8 - 6N | 1/2       | 3/8            | 37.0 | 30.5           | 9.6  | 25.4                | 4,900              | 337 | 2,400 | 165 |
| H - SLCR12 - 8N | 3/4       | 1/2            | 46.5 | 39.6           | 11.9 | 31.8                | 4,600              | 316 | 2,300 | 158 |
| H - SLCR16 - 8N | 1         | 1/2            | 48.8 | 44.5           | 11.9 | 42.9                | 4,400              | 303 | 2,200 | 151 |

## Male Elbow H-SML



### Male NPT Both Ends.

| Part No.      | Pipe Size | L     | d    | H Width Across Flat | Pressure Rating    |     |       |     |
|---------------|-----------|-------|------|---------------------|--------------------|-----|-------|-----|
|               |           |       |      |                     | SS316 Carbon Steel |     | Brass |     |
|               |           |       |      |                     | psig               | bar | psig  | bar |
| H - SML - 2N  | 1/8       | 19.05 | 4.8  | 12.7                | 10,000             | 689 | 5,000 | 344 |
| H - SML - 4N  | 1/4       | 24.50 | 7.1  | 12.7                | 8,000              | 551 | 4,000 | 275 |
| H - SML - 6N  | 3/8       | 26.90 | 9.6  | 17.5                | 7,800              | 537 | 3,900 | 268 |
| H - SML - 8N  | 1/2       | 33.20 | 11.9 | 20.6                | 7,700              | 530 | 3,800 | 261 |
| H - SML - 12N | 3/4       | 35.30 | 15.7 | 25.4                | 7,300              | 502 | 3,600 | 248 |
| H - SML - 16N | 1         | 44.50 | 22.3 | 31.8                | 5,300              | 365 | 2,600 | 179 |

All dimensions are in millimeters unless otherwise specified. Dimensions are for reference only, subject to change.