

Cylinder cabinet

Gas cylinder safety cabinet

DESCRIPTION:

- Safety storage cabinet for the storage of flammable or toxic gas cylinders in working areas for 1 to 4 50 l cylinder according to EN-14470-2
- 90 minutes fire resistance

TECHNICAL DATA:

In accordance with EN 14470-2

Indoor storage	1 to 4 50 l cylinders
Outdoor store	2 to 5 50 l cylinders



- GS-test (EN 14470-1, EN 14727, document EK5/AK4 09-10, ProdSG);
- 50,000 wear-free opening and closing actions;
- Test basis: all cabinets of this model group correspond to the requirements of the Equipment and Product Safety Act (§7 pkt. 1) with respect to the guarantee of safety and health.

FUNCTION / CONSTRUCTION:

- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- Easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- Ventilation: integrated air ducts ready for connection (DN75) to a technical exhaust, even ventilation inside the cabinet
- Tested and certified: according to the stricter GS principles



Indoor version



Outdoor version

Models shown with additional accessories to be ordered separately

ORDERING INFORMATION:

INSIDE MODEL	FLAMABLE AND TOXIC EXTERNAL DIMENSIONS W X D X H (mm)	INTERNAL DIMENSIONS W X D X H (mm)	WEIGHT	CYLINDER
G.90.205.140	1400 x 615 x 2050	1245 x 400 x 1858	690	4
G.90.205.090	900 x 615 x 2050	745 x 425 x 1858	490	3
G.90.205.060.2F	600 x 615 x 2050	477 x 424 x 1858	365	2
G.90.205.060	600 x 615 x 2050	445 x 425 x 1858	365	1
Outdoor				
GOD.215.135	1356 x 400 x 2149	1345 x 370 x 2070	138	5
GOD.215.100	1006 x 400 x 2149	995 x 370 x 2070	113	3
GOD.215.070	706 x 400 x 2149	695 x 370 x 2070	85	2